

VENDOR INSTALLATION INSTRUCTIONS INTERIOR ACCESSORIES PACKAGES

Control Gauges Installation Guide:

- Place 3M Clear Silicone* (not-included) on the back side of the gauges using a toothpick.
- Place the gauges in position and remove any excess silicone. Use painter's tape to hold gauges in place for several hours until the silicone is dry.

Door Pin and Bezel Installation Instructions:

- Remove OEM door pin by rolling down your window and using pliers to unscrew the plastic pin which is threaded.
- Remove the OEM plastic bezel by using a flat-head screwdriver and pulling out the OEM plastic bezel. (This may be completed by using your fingers but is much easier with a screwdriver.)
- Place the new bezel into position and push down over the OEM threaded rod until it is in place.
- Place the new pin on the OEM threaded rod and screw until tight.

Interior Knobs and Cup Holder Installation Guide:

- All interior accessories fit tightly over existing O.E.M equipment.
- As an added measure a very small amount of silicone can be applied to the inside of the knob cover or cup holder to prevent it from being knocked off.

**The vendor recommends clear silicone. If you ever decide to remove the billet aluminum accessory, the silicone will scrape off as opposed to using double-sided tape which may leave a sticky residue.*

STANDARD PACKAGE INCLUDES:

AC Control Knob Covers (2)
Turn Signal/Cruise Control Knob Cover
Windshield Washer Control Knob Cover
Trunk Button Cover
Radio Control Knob Covers (2)
Power Mirror Adjuster Ring
Headlights Control Knob Cover
Door Lock Bezel (2)
Door Lock Pins (2)

DELUXE PACKAGE INCLUDES:

All of the accessories in the Standard Package plus
Cup Holder Kit
Control Gauges Rings (4)